(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 4 August 2005 (04.08.2005)

PCT

(10) International Publication Number WO 2005/071651 A1

(51) International Patent Classification7:

G09G 3/34

(21) International Application Number:

PCT/IB2005/050132

(22) International Filing Date: 12 January 2005 (12.01.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

04100217.1

22 January 2004 (22.01.2004) EP

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for U.S only): JOHNSON, Mark, T. [GB/NI.]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NI.). AILENEI, Neculai [NI./NI.]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). ZHOU, Guofu [NI./NI.]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NI.).
- (74) Agents: ROLFES, Johannes, G., A. et al.; Prof. Holstlaan 6, NL-5656 ΛΛ Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK; LR, LS, LT. LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTROPHORETIC DISPLAY DEVICE



(57) Abstract: A display device (1) comprises electrophoretic particles (8,9) and an image screen comprising an array of display elements comprising a pixel electrode and a second electrode. The display device comprises control means (15) for supplying drive signals to the electrodes. In operation the image is displayed in subsequent frames. The control means comprise a row driver (16) and a column driver (10). Preset signals (53) are in operation supplied to the display elements whereby the preset signals applied to display elements alter between subsequent frames. The control means are arranged to change preset signals between frames in a column-to-column scheme. The means for supplying preset signals are arranged such that for the preset signals to at least a part of the image screen comprising a group of columns and rows only one set of data is transferred for the preset signals for said group.

WO 2005/071651 A1 III